

# How-To Guides

- [Baselining Devices for Consistency and Standardization](#)
- [Building your Network Discovery](#)
- [Collector server creation](#)
- [Create a Query containing Custom Fields](#)
- [Creating a Query](#)
- [Delete a Device](#)
- [Device Seed Discoveries](#)
- [How to audit a Computer](#)
- [How to audit a subnet using a script](#)
- [How to Audit in complex network environments](#)
- [How to Bulk Edit device attributes](#)
- [How to discover a single Device](#)
- [How to Enable LDAP Authentication and Authorization for Open-Audit](#)
- [How to import devices from and export devices to NMIS](#)
- [How to import devices using a spreadsheet](#)
- [How to import NMIS Nodes and run discovery upon them \(deprecated\)](#)
- [How to Schedule Tasks \(Discovery and Reports\) in Open-Audit Enterprise](#)
- [How to Schedule Tasks in Open-Audit](#)
- [How to use Active Directory Discovery](#)
- [How to use Open-Audit Discovery](#)
- [Mark a Device as Retired](#)
- [NMIS and Open-Audit Integrations](#)
- [Process Walk-Throughs](#)
  - [Adding Support for a Language Open-Audit does not Currently Offer](#)
  - [Ansible Collection](#)
  - [Creating, Populating, and Reporting on Custom Fields](#)
  - [Creating Custom Reports](#)
  - [Leveraging Locations to Speed Up Searching and Display](#)
  - [Monitoring Files for Changes](#)
  - [Organizing your Devices and Users](#)
  - [Software Asset Management](#)
- [Removing Defaults and Hardening](#)
- [Reset, Backup and Restore the Open-Audit database](#)
- [Updating Credential Sets](#)
- [Using Open-Audit to NMIS Integrations \(deprecated\)](#)
- [What can I Expect if I Have no Credentials](#)