# **Automating Admin Tasks Including Node Management**

This page summarising some techniques for automating admin, especially node management.

- NMIS Cluster Node Admin
- Get opConfig working on all my nodes
  - Use the opAdmin GUI to bulk edit nodes
    - ° Automating for many nodes using simple scripts and CLI tools
      - Get a list of nodes using node\_admin.pl
        - Using a script to activate nodes for opConfig
    - opConfig Automation with a Primary and Poller Server
      - Credential Sets Created on all Servers in the Cluster
      - Configure the Nodes from the Primary
      - Sync node data in the Cluster

## NMIS Cluster Node Admin

When using an opHA NMIS cluster most node admin is performed on the "Main Primary" server, more details about that @ opHA 3 Redundant Node Polling and Centralised Node Management

# Get opConfig working on all my nodes

The opConfig application runs on the servers which talk to the end devices, you don't need to install opConfig on your primary server to have it function. Some aspects of the node admin for opConfig can be done from the primary server, then sync'd to the pollers.

## Use the opAdmin GUI to bulk edit nodes

The opConfig User Manual includes details on this: opConfig 4 User Manual, if you are using an opHA cluster, you will need to activate the nodes on the primary and then do the discovery on the poller.

In summary, on the primary access the Node Admin tool, https://server.domain.com/en/omk/admin/nodes, and select the nodes.

										(D)
Opmantek Modules <del>-</del>										∰EN - User:
e / Nodes										
les										
Homo			_							_
loine	+	6 📋 🕤	1				Se	arch term	Name	👻 Go 🔉
vodes		Name 🔺	Group	Location	Business Service	Host	Addresses	Activated	Cluster	Status
Change Password		asgard	NMIS9	DataCenter	Core Network	192.168.88.254		🔕 🚯	lab-ms-poller	degraded
Locations		cloudflare	NMIS9			1.1.1.1		O O	lab-ms-poller	degraded
		cloudflare2	NMIS9			1.1.1.1		O O	lab-ms-poller	degraded
Contacts		demo9	NMIS9	Cloud	Web Page	demo9.opmantek.com		٩	Local	degraded
Aonitored Services		dupe_node	NMIS9			8.8.8.8		00	lab-ms-poller	degraded
		eris	NMIS9	DataCenter	Core Network	eris.opmantek.net		٩	Local	unreachable
scalation Policy		lab-ms-poller	NMIS9			127.0.0.1		00	lab-ms-poller	reachable
event Configuration		lab-ms-primary	NMIS9			127.0.0.1		٢	Local	reachable
Polling Policy		midgard	NMIS9	DataCenter	Core Network	192.168.88.253		٢	lab-ms-poller	degraded
	0	thing	NMIS9			1.1.1.1		O O	lab-ms-poller	degraded
MIS Users		thing2	NMIS9			1.1.1.1		O O	lab-ms-poller	degraded
Access Policy		thing3	NMIS9			1.1.1.1		O 😳	lab-ms-poller	degraded
	Showing 1 to 12 of 12 entries									Show 25 -

Then activate them for opConfig, and click OK.

Bulk Editing2nodes						
General Activation Pc	lling Advanced Primary-Poller					
opConfig 🔽	Enabled	•				
opEvents 🗌		•				
	Enabled	•				
	Cancel	ОК				

This will activate many nodes at once and it will all be sent to the necessary poller.

### Automating for many nodes using simple scripts and CLI tools

Scripts are useful when you want things to happen repeatedly, or you have so many things to click on, scripting is faster than clicking.

#### Get a list of nodes using node\_admin.pl

To get a list of nodes is easy, just ask node admin to get you a list.

/usr/local/nmis9/admin/node\_admin.pl act=list

#### You can filter this by a group node nodes by adding group=GROUPNAME

```
/usr/local/nmis9/admin/node_admin.pl act=list group=GROUPNAME
```

#### Using a script to activate nodes for opConfig

The following BASH script will let activate opConfig for all nodes on the primary server, opHA will then synchronise this to all the pollers.

```
#!/usr/bin/env bash
if [ "$1" == "" ]
then
            echo This script will update the opConfig enabled property for all nodes.
            echo give me any argument to confirm you would like me to run.
            echo e.g. $0 runnow
            exit
fi
NODELIST=`/usr/local/nmis9/admin/node_admin.pl act=list`
for NODE in $NODELIST
do
            /usr/local/nmis9/admin/node_admin.pl act=set node=$NODE entry.activated.opConfig=1
done
```

#### This script could be easily modified to work on some nodes, with a pattern match e.g.

NODELIST=`/usr/local/nmis9/admin/node\_admin.pl act=list | grep NODENAMEPATTERN`

NODELIST=`/usr/local/nmis9/admin/node\_admin.pl act=list group=GROUPNAME`

To run the script, create a file with the contents, using your favourite editor, we used the filename enable-opconfig-all-nodes.sh, once created, update the permissions so it is executable, or just run by prefixing with bash.

```
sudo bash enable-opconfig-all-nodes.sh
```

### opConfig Automation with a Primary and Poller Server

#### Credential Sets Created on all Servers in the Cluster

The first step is to create the credential sets on all servers in the cluster, there are API's for doing this, or you can access the GUI and access opConfig, look for the menu option "System Edit Credential Sets".

API details here: opConfig Credential Sets API

### **Configure the Nodes from the Primary**

The following handy BASH script will update all the nodes and set the required OS Info and Connection details for opConfig to operate.

This example would set the details for Cisco devices running NXOS 7.0 using SSH.

This command also sets the Node Context Name and URL, so there is a button in the opCharts GUI and NMIS to be able to access opConfig easily.

You should replace YOURCREDENTIALSET with the relevant credential set for these devices and YOURPOLLERNAMEORFQDN with the FQDN or hostname, e.g. lab-poller.opmantek.net

```
#!/usr/bin/env bash
if [ "$1" == "" ]
then
       echo This script will run opConfig discovery all nodes.
       echo give me any argument to confirm you would like me to run.
       echo e.g. $0 runnow
       exit
fi
NODELIST=`/usr/local/nmis9/admin/node_admin.pl act=list`
for NODE in $NODELIST
do
       # multi line command to make it easier to read.
       /usr/local/nmis9/admin/node_admin.pl act=set node=$NODE \
       entry.activated.opConfig=1 \
       entry.configuration.os_info.os=NXOS \
       entry.configuration.os_info.version=7.0 \
       entry.configuration.connection_info.credential_set=YOURCREDENTIALSET \
       entry.configuration.connection_info.personality=ios \
       entry.configuration.connection_info.transport=SSH \
       entry.configuration.node_context_name="View Node Configuration" \
       entry.configuration.node_context_url=//YOURPOLLERNAMEORFQDN/omk/opConfig/node_info?o_node=\$node_name
done
```

As the example above you could use a filter on the NODELIST statement to filter the nodes.

#### Sync node data in the Cluster

With many node changes, the best option is to trigger opHA to sync all the node data to the pollers. You can access the opHA menu, view each poller and click the "Sync all nodes" and sync all the nodes or you can run the following command on the primary.

```
sudo /usr/local/omk/bin/opha-cli.pl act=sync-all-nodes
```